

Mezzanines. Mezzanines include roof deck (painted white for greater light reflection) and ³/₄" tongue and groove moisture-resistant unfinished resinboard. Pricing of alternate decking surface is available upon request. *Specify clearance height: (01) 8; (02) 9; (03) 10*!

Overall	Overall	Stock
LxW*	Sq. Ft.	Number
16'x11'	176	53056-S
16'x21'6"	346	53064-S
31'5"x11'	347	53100-5
31'5"x21'6"	681	53101-5
47'x11'	517	53302-5
47'x21'6"	1016	53312-5
62'5"x11'	688	53412-5
62'5"x21'6"	1352	53413-5

*NOTE: Above dimensions are nominal, exact dimensions may vary ± 1 ".

53559-S Optional Bar Grating (extra add-on).

Stairs.

36"W stairs meet top deck of mezzanine. Closed tread with open riser. Call for other sizes and types.



Cut-to-width at your facility for a custom fit meeting your specific needs. Side rails easily connect to most Wildeck mezzanine railings providing a seamless barrier. When one side of the gate opens, the other closes for safe access. Integral kickplate keeps objects from falling. Outside width variable from 120–36". Inside width variable from 109¹/₈–25¹/₈". Meets IBC codes, OSHA safety standards, and ANSI MH28.3–2009 standards. Color: safety yellow. Made in USA. 5727800-T

Accessories.

Specify: (01) 2 rail, (02) 3 rail, (03) single rail expanded metal

Description	Stock Number
Handrail/ Kickplate	53575-S*
Stair Landing	53647-5
6'W swing gate	53702-S

Safety Tilt Gate. Pulls back and lifts out keeping employees away from mezzanine edge. Lightweight tube construction. Includes: protective kick plate and spring-loaded latches. 75% "Wx42"H overall. 72" usable opening width.

53574-S





Mezzanines allow you to:

- Increase your storage space
- Create a work platform
- · Add an in-plant office
- Renovate existing warehouse space

Double your useable floor space with a cost-effective pre-engineered mezzanine from the largest mezzanine manufacturer in the United States. Suitable for industrial and commercial applications. Heavy-duty mezzanines feature minimum 5x5, ³/₁₀" thick columns with 12" base plates and 125psf uniform live load capacity. Easy installation with easy-to-follow instructions that require no drilling or welding. 25-year performance guarantee. Made in USA.